

MV VOLTAGE REFLECTOR LED LAMPS-JDR



Product Features:

Main Voltage supply, Long service life, low power consumption, energy saving. Shockproof, moisture proof, anti-distortion

Primary Application:

Direct replace traditional JDR Reflector Halogen Lamp as Spot light, Decoration lighting for indoor and outdoor use

Part No.	Volt (VAC)	Wattage (W)	Led nos. (pcs)	Wave length (nm)or TC(k)	Luminous Flux	Luminance (LUX)	Emitting Color
LED-GU10-12-R	110/220	0.7-1.1	12	610-630	3-7	20-30	Red
LED-MR16-15-R	110/220	0.7-1.1	15	610-630	4-8	25-35	Red
LED-MR16-18-R	110/220	0.8-1.2	18	610-630	5-9	30-40	Red
LED-MR16-21-R	110/220	0.8-1.2	21	610-630	6-10	35-45	Red
LED-MR16-12-G	110/220	0.8-1.2	12	510-530	12-17	130-150	Green
LED-MR16-15-G	110/220	0.8-1.2	15	510-530	15-20	140-160	Green
LED-MR16-18-G	110/220	0.9-1.3	18	510-530	18-23	150-190	Green
LED-MR16-21-G	110/220	0.9-1.3	21	510-530	20-25	160-200	Green
LED-MR16-12-B	110/220	0.8-1.2	12	465-475	4-8	40-60	Blue
LED-MR16-15-B	110/220	0.8-1.2	15	465-475	5-9	60-80	Blue
LED-MR16-18-B	110/220	0.9-1.3	18	465-475	18-23	150-190	Blue
LED-MR16-21-B	110/220	0.9-1.3	21	465-475	7-11	90-110	Blue
LED-MR16-12-Y	110/220	0.7-1.1	12	585-595	3-7	30-40	Yellow
LED-MR16-15-Y	110/220	0.7-1.1	15	585-595	4-8	35-45	Yellow
LED-MR16-18-Y	110/220	0.8-1.2	18	585-595	5-9	40-50	Yellow
LED-MR16-21-Y	110/220	0.8-1.2	21	585-595	6-10	45-55	Yellow
LED-MR16-12-W	110/220	0.8-1.2	12	7000-9000K	14-18	140-180	White
LED-MR16-15-W	110/220	0.8-1.2	15	7000-9000K	18-25	150-190	White
LED-MR16-18-W	110/220	0.9-1.3	18	7000-9000K	20-30	160-200	White
LED-MR16-21-W	110/220	0.9-1.4	21	7000-9000K	25-35	180-220	White
LED-MR16-18-MC	110/220	0.6-0.8	18	610-630/510-530/465-475	0.5-8	/	Muti color change

Remark:

- Base E14S E27
- Indoor use only.
- Traditional electronic transformer is not applicable.
- Voltage:AC220V±10V or AC110V±10V.
- Illuminate data are tested at distance of 1 meter
- Working Environment: -20℃-40℃
- Storage Condition: -20℃-85℃

