

M-4010-360KV					
Lipo	PROP	V	A	RPM	TRUST(g)
3S	TL2830 14*5.5	11.13	4.34	3650	550
	TL2831 15*5.5	11.1	6	3475	925
	TL2813 15*5.5	11.22	4.78	3600	675
	TL2834 15*7.5	11.11	4.45	3600	600
	TL2814 16*5.0	11.12	8.83	3275	925
	TL2835 16*5.5	11.15	8.16	3325	925
	TL2815 17*5.5	11.11	7.48	3400	975
	TL2822 18*5.5	11.1	10.23	3175	1200
Lipo	PROP	V	A	RPM	TRUST(g)
4S	TL2828 12*5.5	14.82	4	4925	525
	TL2829 13*5.5	14.82	5.68	4775	850
	TL2830 14*5.5	17.85	7.19	4675	975
	TL2831 15*5.5	14.8	10	4400	1300
	TL2813 15*5.5	14.85	7.69	4600	1125
	TL2834 15*7.5	14.82	7.26	4625	1050
	TL2814 16*5.0	14.8	14	4100	1400
	TL2835 16*5.5	14.81	12.92	4175	1475
	TL2815 17*5.5	14.8	11.63	4275	1600
	TL2822 18*5.5	14.85	15.75	3975	1850
Lipo	PROP	V	A	RPM	TRUST(g)
5S	TL2827 11*5.5	18.53	4.33	6150	600
	TL2828 12*5.5	18.51	5.77	6000	850
	TL2829 13*5.5	18.52	8.39	5800	1225
	TL2830 14*5.5	18.55	10.75	5550	1450
	TL2831 15*5.5	18.5	14.87	5225	1900
	TL2813 15*5.5	18.53	10.86	5525	1625
	TL2834 15*7.5	18.53	10.7	5575	1550
	TL2814 16*5.0	18.5	21.05	4750	1950
	TL2835 16*5.5	18.54	19.21	4925	2075
	TL2815 17*5.5	18.5	16.78	5100	2275
	TL2822 18*5.5	18.52	21.62	4675	2650

Lipo	PROP	V	A	RPM	TRUST(g)
	TL2826 10*5.5	22.32	3.72	7525	575
6S	TL2827 11*5.5	22.27	6	7250	950
	TL2828 12*5.5	22.27	8.11	7050	1225
	TL2829 13*5.5	22.29	11.5	6750	1675
	TL2830 14*5.5	22.53	15.3	6475	2100
	TL2831 15*5.5	22.57	20.65	6050	2700
	TL2813 15*5.5	22.3	14.56	6450	2175
	TL2834 15*7.5	22.19	14.47	6425	2100
	TL2815 17*5.5	22.13	22.02	5725	2925