



HDMI REPEATER USER INSTRUCTION

Indication

- ①  Green Light Power Indicator
- ②  Yellow Light Malfunction Indicator
- ③ "Display" Connection port to signal receiver
- ④ "Source" Connection port to signal source



Installation

Step 1. Connect the cable from signal receiver to the repeater marked with "Display"
Signal receiver: such as HDTV, Projector, etc.



Step 2. Connect the cable from signal source to the repeater marked with "Source"
Signal source: such as DVD player, Set Top Box, Satellite, etc.

Step 3. Turn on the power of signal receiver and signal source.

**For better performance, place the repeater as close to the receiver side as possible.

Trouble Shooting

Please make sure all cables are workable before connecting to the repeater.

		Possible reason	Countermeasure
on	off	The repeater works functional	
on	on	Wrong signal direction No cable on signal receiver side No power at signal receiver side Cable length too long	Change the signal direction Connect the cable Power on the receiver device Change and reduce the cable length
off	on	Wrong signal direction and No cable on signal source side	Change the signal direction and Connect the cable
off	off	No power both sides No cable connected both sides	Turn the power on Connect cables

Specification

Power: The repeater uses the power from the appliance, no external power required.

Compatible with DTV resolutions : 480I 、 480P 、 720P 、 1080I 、 1080P

Compatible with Computer resolutions : VGA 、 SVGA 、 XGA 、 SXGA 、 UXGA

Operating Temp.: 0°C to 50°C (32°F to 122°F)

Dimension: 55.6mm(L)×42.0mm(W)×21.5mm(H)/without bracket

55.6mm(L)×46.0mm(W)×23.3mm(H)/with bracket

Weight : 45g (without bracket)

Accessory : Mounting Bracket×1

Mounting Screw×2

Velcro Tape (Reclosable Tape)×1